


RF10000
Remote Radio Frequency
Point Level Control
Installation & Operation Manual



150 Venture Boulevard
Spartanburg, SC 29306
Phone: (864) 574-8060, Fax: (864) 574-8063
Customer Service: (800) 778-9242
Internet: www.bindicator.com
email: sales@bindicator.com

RF-10000
Remote Radio Frequency Point Level Control
Installation and Operation Manuals
4/97 Rev. C LRF180024

Section	Description	Page
1.0	INTRODUCTION	2
2.0	OPERATING THEORY	2
3.0	AVAILABLE MODELS	2
4.0	SPECIAL FEATURES	2
5.0	SPECIFICATIONS	2
	5.1 <i>Electronics</i>	3
	5.2 <i>Standard Duty Probe</i>	3
	5.3 <i>Heavy Duty Probe</i>	4
	5.4 <i>Flush/Probe Dome Flush Probe</i>	4
	5.5 <i>Stub Probe</i>	4
	5.6 <i>Food Grade Probe - Threaded Connector</i>	4
	5.7 <i>Standard Duty Probe - Kynar * Coated</i>	4
	5.8 <i>Heavy Duty Probe - Kynar* Coated</i>	4
	5.9 <i>Food Grade Probe - Sanitary Connector</i>	4
	5.10 <i>Ceramic Probe</i>	4
		5
6.0	INSTALLATION	5
	6.1 <i>Probe Location and Mounting</i>	6
	6.2 <i>Probe Installation and Hookup</i>	6
	6.3 <i>Electronics Location and Mounting</i>	6
	6.4 <i>Electronics Installation and Hookup</i>	6
	6.5 <i>Fail-Safe Selection</i>	6
	6.6 <i>Sensitivity Setting</i>	6
	6.7 <i>Time Delay Setting</i>	7
	6.8 <i>Calibration.</i>	9
	6.9 <i>Verification</i>	9
	6.10 <i>Function Test</i>	9
		10
7.0	TROUBLESHOOTING	10
	7.1 <i>Installation Errors</i>	11
	7.2 <i>Application Errors</i>	11
	7.3 <i>Factory Assistance</i>	11
		11
8.0	WARRANTY & PARTS	11
	8.1 <i>Warranty</i>	12
	8.2 <i>Electronics Replacement</i>	12
	8.3 <i>Parts List</i>	12
		12
9.0	DRAWINGS	12
10.0	MODEL SELECTION	12
	10.1 <i>RF-10000 Remote Unit - Electronics</i>	13
	10.2 <i>RF-10000 Remote Unit - Probes</i>	14
	10.3 <i>RF-10000 Remote Cable Assembly</i>	14
	10.4 <i>RF-10000 Bulk Cable - Unterminated</i>	15
	10.5 <i>RF-10000 Lagging Model Assembly</i>	15
	10.6 <i>RF-10000 Probe Pipe Assembly</i>	15
		15
		15

Important!
Do not dispose of the carton or packing material until the unit has been inspected for damage.
If the unit is received damaged, notify the carrier or the factory for instructions.
Failure to do so may void your warranty.
Thank you!

SPECIAL NOTE

The electronics furnished with your RF10000 series level control are a newer design than what you may have purchased in prior years. The new **“Design Level 2” electronics** include the following improvements:

- **DIP switch sensitivity settings...**we now have 8 sensitivity settings versus 3 jumper selections, that were part of the original design. This feature allows you to sense a wider range of materials with one electronic unit.
- **DIP switch time delay settings...** we now have 4 time delay settings versus 3 jumper selections, that were part of the original design. This feature gives you the flexibility to change time delay from 1 second (min.) to 7 seconds (max.), depending on your process.
- **“Latched” internal calibration push-button...**A momentary push of the calibration button now initiates calibration. You no longer have to hold the button down and wait for the calibration light to illuminate.
- **“Euro style” terminal block...**which is capable of terminating two - 14 gauge wires. This “safer design” will help protect your personnel or electricians when connecting power to our unit.

These features are explained in more detail within this manual.

1.0 INTRODUCTION

The RF-10000 Series level control is a point level device used to detect the presence or absence of material at a point inside a tank, bin, or other vessel. The electronics are remote and the probe is connected by a coaxial cable.

Material coming in contact with the RF-10000's probe causes its output relay to change state, thereby indicating to the user material presence.

The RF-10000 utilizes the PRO-GUARD® principle to prevent false indications from material coating or moisture and condensation on the probe. The RF-10000 Series also has the EZ-CAL® feature which make calibration easy and accurate. This features also allows the units to be remotely calibrated through a remote module or a computer.

2.0 OPERATING THEORY

The RF-10000 is a relatively low-powered device requiring approximately 4 watts for operation. The power supply can accept 120 VAC, 240 VAC, or 24VDC input power. (All are factory selectable.) A 153.6 KHZ RF oscillator provides the signal which is directed to both the PRO-GUARD® and active sensing area of the probe. (See Figure 1.)

Detection circuitry compares the signal from the active sensing area to a reference RF signal. Since all materials have dielectric constants (relative permittivity) and conductance values different from air, the impedance of the signal changes when material touches the probe. This change causes a shift in phase of the RF signal. A phase difference between the active signal and reference signal causes output circuitry to operate.


Sensitivity selection determines how much phase shift is needed before the output relay changes state. Time delay selection determines how much time should elapse after detection until the output relay changes state. Fail-safe selection determines whether the relay energizes or de-energizes when material is present.

3.0 AVAILABLE MODELS

Various Electronic and Probe configurations can be found in the **RF "Elite" Series Guide** (LRF180019). It is critical that the Electronic Model Number and Probe Number be recorded for convenience if replacement parts are required.

4.0 SPECIAL FEATURES

All RF-10000 Series units have solid-state electronics, with pushbutton calibration, fail-safe output indication, time delay selection, polyester coated aluminum housing, and PRO-GUARD® probes.



A very important feature of the RF-10000 is the ability to ignore the effects of coatings that can adhere to the sensing probe. In most applications, a certain amount of the material that is being sensed will adhere to the sensing probe after a period of time. This can be due to the nature of the material itself or to condensed moisture that can cause dry material to bond to the probe's surface.

Bindicator's PRO-GUARD® disregards the effects of probe coating and only indicates that material is present when the actual mass of material (either dry or liquid) in the bin comes in contact with the probe.

Figure 2 shows the PRO-GUARD® probe. The drive current to the PRO-GUARD® electrode is at the same frequency and polarity as the probe. When a coating forms on the probe, the RF current from the PRO-GUARD® tends to saturate that portion of the built-up material near the wall so that little or no RF current can flow from the probe to the wall. When the actual bulk material in the bin fills to the point where the material is touching the probe, current from the probe will flow around the saturated region and indicate material presence.




Figure 2

5.0 SPECIFICATIONS

5.1 Electronics

- Line Voltage: 120VAC ± 15%, 240VAC ±15%, 50/60 Hz, 24 VDC
- Power: 4 Watts
- Output Relay: DP/DT, 5 amps at 115VAC
- Temperature Range: -40° F. to + 160° F. (-40° C. to +72° C.)
- *Sensitivity Settings: See Section 6.6
- Selectable Time Delay: See Section 6.7
- Calibration: Pushbutton Electronic with Remote Capability

*Unit has a high sensitivity electronic board with .5 pf rating when "A" is in model code.

5.2 Standard Duty Probe

- Dimensions: See Installation Drawing
- Mounting: 3/4" NPT - 316 S.S. Or 1 1/4" NPT Aluminum
- Probe Materials: 316 S. S. and Ryton*
- Probe Temperature: -100° F. to +450° F. (-73° C. to +232° C.)
- Pressure: Up to 150 psi (10.5 kg/cm²)

*Trademark of Phillips Chemical Company, Subsidiary Phillips Petroleum

5.3 Heavy Duty Probe

Dimensions: See Installation Drawing
Mounting: 3/4" NPT - 316 S.S. or 1 1/4" NPT Aluminum
Probe Materials: 316 S. S. and Ryton®*
Probe Temperature: -100° F. to + 450° F. (-73° C. to +232° C.)
Pressure: Up to 150 psi (10.5 kg/cm²)

5.4 Flush Probe/Dome Flush Probe

Dimensions: See Installation Drawing
Mounting: 9/32" Dia. Hole on 7 7/16" Bolt Circle - 6 Places
Probe Materials: 316 S. S. and Epoxy
Probe Temperature: -30° F. to +200° F. (-34° C. to +93° C.) Continuous
-30° F. to +250° F. (-34° C. to +121° C.) Intermittent
Pressure: Up to 50 psi (3 kg/cm²)
Note: Not for use in liquid service

5.5 Stub Probe

Dimensions: See Installation Drawing
Mounting: 3/4" NPT - 316 S.S. or 1 1/4" NPT Aluminum
Probe Materials: 316 S. S. and Polysulfone
Probe Temperatures: -30° F. to +300° F. (-34° C. to +149° C.)
Pressure: Up to 150 psi (10.5 kg/cm²)

5.6 Food Grade Probe - Threaded Connector

Dimensions: See Installation Drawing
Mounting: 3/4" NPT - 316 S.S. or 1 1/4" NPT Aluminum
Probe Materials: 316 S. S. and Polysulfone
Probe Temperatures: -30° F. to +300° F. (-34° C. to +149° C.) Continuous
Pressure: Up to 150 psi (10.5 kg/cm²)

5.7 Standard Duty - Kynar® Coated

Dimensions: See Installation Drawing
Mounting: 3/4" NPT Teflon® Coated Connector
Probe Materials: 316 S. S. and Ryton® Coated with Kynar®
Probe Temperatures: -100° F. to +250° F. (-73° C. to +121° C.)
Pressure: Up to 50 psi (3.5 kg/cm²)

5.8 Heavy Duty - Kynar® Coated

Dimensions: See Installation Drawing
Mounting: 3/4" NPT Teflon® Coated
Probe Materials: 316 S. S. and Ryton® Coated with Kynar®
Probe Temperatures: -100° F. to +250° F. (-73° C. to +121° C.)
Pressure: Up to 50 psi (3.5 kg/cm²)

5.9 Food Grade Probe - Sanitary Connector

Dimensions:	See Installation Drawing
Mounting:	Mates with Size 1 Cherry Burrel "S" Line® or Ladish Tri-Clamp®
Probe Materials:	316 S. S. with Polysulfone
Probe Temperatures:	-30° F. to +300° F. (-34° C. to 149° C.)

5.10 Ceramic Probe

Dimensions:	See Installation Drawing
Mounting:	1/4" NPT
Probe Materials:	304 S.S. and ceramic
Probe Temperature:	-40° F. to +1000° F. (-40° C. to 538° C.)
Pressure:	Up to 30 psi (2 kg/cm ²)

*Trademark of Pennwalt

**Trademark of DuPont

Various RF models are available which have been "Listed" as complete assemblies by Underwriters Laboratories or CSA approved for use in Class I, Div. I, Groups C & D and Class II, Div. I, Groups E, F, & G atmospheres.

To be Listed by UL and approved by CSA these units must contain special intrinsic safety barriers to limit the amount of energy on the probe itself in the event of a failure in the electronics. UL, FM and CSA also requires a special assembly of the probe to the electronic housing. Because of this special probe seal, the Explosionproof Models are dimensionally different from the General Purpose Units.

The same dimensional difference exists for Coated Standard, Food, Stub, and Coated Heavy Duty. No dimensional difference exists in the Flush Probe units.

On explosionproof units, an approved conduit seal fitting must be installed within 18 inches of conduit opening.

CAUTION: When mounting explosionproof units, never adjust the orientation of the probe or probe housing by turning the housing section. This will break internal wires and permanently damage the probe.

For tightening units with threaded bin connections, the unit must be positioned by using a wrench on the bin connector. Wrench size required is 1 1/16" with open end.

For "Flush Mount" probe units, the position must be adjusted by removing the mounting bolts and moving the entire probe and housing.

6.0 INSTALLATION

6.1 Probe Location and Mounting

The probe should be located out of the direct flow of material into the vessel. Protective shields or an offset mounting procedure may be required. Please consult the factory for special mounting problems.

Note: Use caution when preparing all wires for connection to terminal block. Strip the insulation a maximum of 1/4 inch (6mm) or use insulated ferrules such as Altech 8969.0 or Altech 2206.0 to prevent shorting of conductors.

6.2 Probe Installation & Hookup

Field wiring should conform to the requirements of the National Electrical Code and any other agency or authority having jurisdiction over the installation. **On multiple installations, the coaxial cable must remain separated in individual conduits and raceways.** After mounting the probe, make sure there is a good electrical connection between the process connection and the vessel wall. **Refer to the drawings listed in Section 6.0 for proper installation and hookup and wiring instructions.**

CAUTION: When mounting explosionproof units, never adjust the orientation of the probe or probe housing by turning the housing section. This will break internal wires and permanently damage the probe.

For tightening units with threaded bin connections, the unit must be positioned by using a wrench on the bin connector. Wrench size required is 1 1/16" with open end.

For "Flush Mount" probe units, the position must be adjusted by removing the mounting bolts and moving the entire probe and housing.

6.3 Electronics Location and Mounting

Field wiring should conform to the requirements of the National Electrical Code and any other agency or authority having jurisdiction over the installation.

Note: Use caution when preparing all wires for connection to terminal block. Strip the insulation a maximum of 1/4 inch (6mm) or use insulated ferrules such as Altech 8969.0 or Altech 2206.0 to prevent shorting of conductors. Tighten screws in terminal block to 4 in/lbs.

Note: Maximum cable distance from electronics to the probe on General Purpose Units cannot exceed 75 feet (23m). Maximum cable distance from electronics to the probe on Explosion-proof Units cannot exceed 50 feet (15.24m).

6.4 Electronics Installation and Hookup

Refer to Drawings Listed in Section 6 for proper wiring and hookup instructions.

Note: Cut remote cable to appropriate length. Do not coil excess cable. Do not wrap excessive cable around electronics in or out of the enclosure.

6.5 Fail-Safe Selection

The RF-10000 is shipped from the manufacturer in the high level fail-safe condition.


High Level Operation - If the electrical power fails, the relay turns off. This indicates material as if the tank were full.

Relay Light Logic Relay Light on - no material present
 Relay Light off - material present

Low Level Operation - If electrical power fails, the relay turns off. This indicates no material as if the tank were empty.

Relay Light Logic Relay Light on - material present
 Relay Light off - no material present

Note: If low level failsafe is desired, then clip the High Level Failsafe jumper located on the lower RF-10000 circuit board. (See Figure 3)




The relay contact terminals on TB 2 are labeled in the powered, unalarmed state. This status may be opposite that of other brands of level controls. Contacts as marked on TB2 are not the relays nomenclature, but are marked so contacts are in "normal" positions when unit is powered and unalarmed.

Maintenance Note

A replaceable coin-type lithium battery is used to help maintain calibration data in the RF electronic unit. Recommended maintenance is replacement after every 3 years of operation. The battery is located on the Power Printed Circuit Board Assembly, just under the corner of the Light Printed Circuit Board Assembly. (See Figure #3) To remove, simply lift the edge of the battery and slide it from the holder. To replace, slip the new battery in under the contact arm until the new battery is firmly seated into the holder. As replacement, use ONLY lithium coin-type battery #CR1620 (Bindicator part # LUC036952).

Figure 3
(Electronic Unit with Function Test)



6.6 Sensitivity Setting

Due to variations in material characteristics, correct sensitivity selection is critical to assure proper unit operation. This can be field programmable to one of the eight predetermined settings. (see **Figure 3**)

High Sensitivity Hard to detect materials such as plastic pellets, light powders, dry grains

Med. Sensitivity Most dry or liquid materials such as cement, petroleum products, flour

Low Sensitivity Most liquid solutions such as aqueous solutions, acids

Note: The RF-10000 is shipped from the manufacturer in the high sensitivity condition. Selection is made by changing the DIP switch settings.

switch 1 off and switch 2 off and switch 3 off = 1 Pf High
switch 1 on and switch 2 off and switch 3 off = 1.5 Pf
switch 1 off and switch 2 on and switch 3 off = 2.0 Pf
switch 1 on and switch 2 on and switch 3 off = 3.0 Pf Medium
switch 1 off and switch 2 off and switch 3 on = 10.0 Pf Low
switch 1 on and switch 2 off and switch 3 on = 12.0 Pf
switch 1 off and switch 2 on and switch 3 on = 14.0 Pf
switch 1 on and switch 2 on and switch 3 on = 15.0 Pf Low/Low

6.7 Time Delay Selection

When the RF-10000 is used in liquid or agitated material where material movement could cause false or premature level indication, an increased time delay selection may be desirable.

Note: The RF-10000 is shipped from the manufacturer in the minimum time delay condition. Increased time delay selection is made by changing the DIP switch setting.

switch 1 off and switch 2 off = 1 second minimum
switch 1 on and switch 2 off = 2 seconds
switch 1 off and switch 2 on = 4 seconds
switch 1 on and switch 2 on = 7 seconds maximum

6.8 Calibration

CAUTION: MATERIAL MUST BE WELL BELOW PROBE BEFORE CALIBRATION PROCEDURE BEGINS.

Prior to operation, the RF-10000 must be calibrated in order to match the operating characteristics of the vessel. Unit may be calibrated either locally at the electronic unit or at a remote location if the RF-10000 was supplied with either the remote calibration module option or the remote keyswitch module option.

CAUTION: If unit is calibrated with material in contact with the probe, the unit will not calibrate.

CAUTION: If unit is calibrated with material in contact with the probe, the unit will not calibrate.

A. Local Calibration - Momentarily press the calibration push-button. The green calibration light comes on when calibration is complete. Calibration is now complete. The green calibration LED should remain on. Recalibrate any unit whose green calibration light is off.

NOTE: Calibration should be completed within 5 to 30 seconds. Consult factory if calibration time is not within this range.

B. Remote Calibration Module -When the remote calibration module is used, press and release the push button on the module. The integral light will come on indicating that the calibration sequence has been initiated. When the light goes out, calibration is complete. (see Drawing LRF180107).

C. Remote Keyswitch Module -When the remote keyswitch module is used, turn the key toward the "Calibrate" position and release. The integral light will come on indicating that the calibration sequence has been initiated. When the light goes out, calibration is complete. For hookup, refer to Drawing B-LRF180108 at the back of this manual.


6.9 Verification

Raise and lower material level and observe relay indicating LED for verification of proper operating condition. If the unit fails to detect the material, a higher sensitivity setting may be needed. If the unit falsely indicates material presence, a lower sensitivity setting may be needed.

6.10 Function Test

Set Function test selection jumper to the same setting as the sensitivity selection. (Example: If sensitivity selection is "HIGH" - then position the function test jumper in the middle positions

If sensitivity selection was a setting between High and Medium, then set the test in the Medium position. If sensitivity selection was a setting between Medium and Low, then set the test in "Low" position.



Pushing the "function test" button or turning the optional remote keyswitch to the "Test" position will initiate a test of the unit. This test is only practical when material level is below the probe. If the unit is in calibration and capable of sensing material at the probe, the output relay will go into the "Alarm State" on units in "High Level Failsafe". On units where the High Level Failsafe jumper has been cut (unit in Low Level Failsafe), the unit will unalarm.

7.0 TROUBLE SHOOTING


7.1 Installation Errors

Probe should be located out of the direct flow of material while the vessel is being filled.

See Figure 5. Unit should be mounted with the conduit opening down and located, if possible, higher than the conduit raceway. This will eliminate the possibility of moisture settling in the conduit outlet box. If the conduit is higher than the unit, provide a conduit loop under the conduit outlet box with a conduit drain fitting.

Mounting the probe in a nozzle or location where material bridges excessively may cause false indication. The probe should be mounted so

material does not buildup excessively over the PRO-GUARD® area of the probe. **See Figure 1.** If the probe is mounted in a nozzle or nipple, the PRO-GUARD® area must be inside the vessel.



Vertical mounting reduces bridging problems. If material to be sensed is of a nature where a buildup will continue to grow on the probe, vertical mounting is necessary.

7.2 Application Errors

Extreme Material Buildup - Use in materials where a continually, growing buildup of a conductive material will occur should be avoided. The PRO-GUARD® will prevent false indication from material coating and condensation, but a continually, increasing buildup will eventually exceed even the PRO-GUARD® capability.

Highly Corrosive Materials - Wetted probe parts consist of 316 S.S. and Ryton (or applicable material according to selected probe.) The conduit outlet box is constructed in aluminum. If you believe the materials in contact with the probe or mounting may cause corrosion with aluminum, Ryton or 316 S.S., consult the factory.

Extremely Light and Dry Materials - Use in very light materials (less than 30 lbs./cu. ft.) and very dry, non-conductive materials (less than 3% moisture) may require higher sensitivity electronics or sensitivity attachments to the probe.

7.3 Factory Assistance

If attempts to locate any difficulties with the unit fail, notify your local factory representative. To help solve your problem quickly, please have as much of the following information as possible:

- Model Number
- Date Purchased
- Brief application information such as, material to be detected, approximate vessel size and location of unit(s) in the vessel.
- Brief description of the problem such as, fails to detect material, or intermittent false alarms.
- What investigation has been performed by the user and what was discovered.

If your local representative is unable to determine the cause of your difficulty, they will refer you to a factory engineer. Equipment shipped back to the factory without proper authorization will be refused and returned at the shipper's expense.

8.0 WARRANTY & PARTS

8.1 Warranty

Refer to Manufacturer's General Terms and Conditions of Sales for Warranty information.

8.2 Electronics Replacement

Replacement electronics are readily available for your RF Model. There are two methods to determine the correct Part Number of your electronic unit.

1. Call Bindicator Customer Service Department with the Model Number of your unit. They will search our database and advise you of the Part Number.
2. Find the Serial Number located on the bottom side (where the probe wires connect) of the electronic unit. The Serial Number is written with black permanent marker. The first three digits of the Serial Number are the last three digits of the Part Number. Just add the prefix LRF110 to these three numbers and you have the Part Number. Example: Serial Number reads 302-9326-05, thus the Part Number is LRF110302.

8.3 Parts List

The RF-10000 is designed to give years of unattended service. No scheduled maintenance or parts service is required.

9.0 DRAWINGS

<u>Description</u>	<u>Drawing No.</u>
Probe Cable Termination Extended/Lagged Assemblies	B-LRF110025
Remote Cable Termination Assemblies	B-LRF110028-C
Probe Accessories	B-LRF180106
RF Pushbutton Remote Cal. Module	B-LRF180107
RF Keyswitch Module	B-LRF180108
General Purpose Installation/Hookup Drawing DL2 E/U	B-LRF180127
Remote Probe with Type "S" Mounting	B-LRF180130
Extended, Remote Probe G/P and X/P	B-LRF180137
Remote Probe G/P with Type "A" Mounting	B-LRF180138
Remote Probe UL X/P	B-LRF180139
Remote Probe UL X/P with Type "S" Mounting	B-LRF180140
Remote FLush Probe G/P and X/P	B-LRF180141
Remote Stub Probe G/P with Type "A" Mounting	B-LRF180142
Remote Dome Flush Probe GP/XP	B-LRF180143
Lagged Remote Probe G/P and X/P	B-LRF180144
Remote Ceramic Probe	B-LRF180146
RF10000 Dimensional Electronic Enclosure	B-LRF180147
RF10000 Explosionproof Probe Installation/Hookup Dwg Design Level 2	B-LRF180148

10.0 MODEL SELECTION for Design Level 2 Units

10.1 RF-10000 Remote Unit - Electronics

RF10 - E - - - -

<p><u>Voltage</u> 1 = 120VAC 2 = 240VAC 3 = 24VDC 4 = 12VDC 5 = 24VAC 6 = 48VAC</p> <p><u>Enclosure Type</u> G = General Purpose NEMA 4/5 (Note 1) X = Explosionproof NEMA 7, 9 (Note 2) S = NEMA 4X, 304 S.S. (Consult Factory) B = Explosionproof NEMA 7, 9 BASEEFA (Note 2)</p> <p><u>Probe Requirement</u> 1 = Single Probe 2 = Dual Probe</p> <p><u>Electronics</u> C = Standard Sensitivity With Functional Test D = Sensitivity Modification (.5 pf) With Functional Test K = Standard (1pf) Sensitivity For Dome Flush Probe with Functional Test</p> <p><u>Electronic Unit (Probe & Cable Are Separate Items)</u></p>
--

RF-10000 Radio Frequency Type Series

Note 1: The total length of cable can not exceed 75 feet (23m) from the electronics.

Note 2: **Maximum cable distance** between electronics and probe on explosionproof units is 50 feet (15.24m).

Note 3: Order Probe and Cable as a separate item.

10.2 RF-10000 Remote Unit - Probes

RF10 - P - - - - 1 - __ (See Note 1 Below)

Enclosure Material

1 = Bindicator Standard Enclosure

Enclosure Type

G = General Purpose

X = Explosionproof (See Note 7 and 8)

E = NEMA 4X, Epoxy

S = NEMA 4X, 304 S.S.

B = Explosionproof NEMA 7, 9 (BASEEFA)

Probes

0 = Standard

1 = Standard, Kynar® Coated

2 = Food Grade

3 = Ceramic (Specify "D" Configuration)

4 = Stub

5 = Heavy Duty

6 = Heavy Duty, Kynar® Coated

7 = Dome Flush Mount (Config, "A" & Electronics "K" Only)

(Thickness To Be Specified) - See Note 2 Below

8 = Flush (Use "A" Configuration Only)

A = Armored Food Grade (Use "A" Configuration Only)

Configuration

A = Standard With 3/4" Threaded Connector & Flush Mount. (See Notes 3 and 6)

B = Pipe Extended Probe - S.S. Parts (See Notes 4 and 6)

C = Pipe Extended Probe - Plated Parts (See Notes 4 and 6)

D = Lagged Probe - S.S. Connector/Plated Coupling. (See Notes 5 and 6)

S = Sanitary Connector

Remote Probe Assembly (Electronics & Cable Are Separate Items)

RF Remote Radio Frequency Type Series

Note 1: For 3A Sanitary Certification, add "3A" at end of the Model Code. Configuration "S" must be used and either "Type 2" Food Grade probe or "Type 4" Stub probe.

Note 2: Thickness of probe must be specified: 3/8", 1/2", 5/8" or 3/4" wall thickness.

Note 3: For 1 1/4" mounting, order LUB042397 reducer bushing with unit.

Note 4: Order Extensions as a separate item.

Note 5: Order Lagging as a separate item.

Note 6: Order Remote Cable as a separate item.

Note 7: Units have been listed as a complete assembly by UL for use in Class 1, Div 1 Groups C & D, Class II Div 1, Groups E, F and G. These probes contain intrinsic safety barriers and can only be used with electronics which are designated explosionproof, even if the electronics are in an area that is nonhazardous.

Note 8: Consult factory to see if the specified assembly configuration is included in the agency's listing or Approval.

10.3 RF-10000 Remote Cable Assembly

Cable - Factory Assembled

RFC - _____ - _____

Length In Feet

Cable Type

A = High Temperature (+450° F.) (+232° C.)

B = Low Temperature (+160° F.) (+71° C.)

Remote Cable Model Assembly

Special Note: Individual conduit is required for each cable. DO NOT INSTALL MORE THAN ONE CABLE in a conduit or raceway or along with other conductors. The maximum distance between the electronics and probe on explosionproof units is 50 feet (15.24m) and on general purpose units is 75 feet (23m).

10.4 RF-10000 Bulk Cable - Unterminated

Product Code	Description
LUC035208	Low Temperature (+160° F.) (+71° C.)
LUC035209	High Temperature (+450° F.) (+232° C.)
LRF110039	Termination Kit

10.5 RF-10000 Lagging Model Assembly

RFL - _____ - _____

Pipe Lagging Length In INCHES

Material Designation

A = Galvanized Pipe - High Temperature Cable +450°F (+232°C)

B = Galvanized Pipe - Low Temperature Cable +160°F (+71°C)

Lagging Model Assembly (If over 6" pipe) (15.24 cm pipe)

10.6 RF-10000 Probe Pipe Extension Assembly

RFE - _____ - _____

Extension Length In INCHES

Material

A = Galvanized Pipe - High Temperature Cable (+300° F.) (+148° C.)

B = Galvanized Pipe - Low Temperature Cable (+160° F.) (+71° C.)

C = 316 S. S. Pipe - High Temperature Cable (+300° F.) (+148° C.)

D = 316 S. S. Pipe - Low Temperature Cable (+160° F.) (+71° C.)

Extension Model Assembly

- Note 1. Max. probe temperature on pipe extended models cannot exceed 300° F. (148° C.)
- Note 2. Pipe extended models can mount only in a 1 1/4" NPT coupling.
- Note 3. Because the pipe extended unit is mounted in 1 1/4" NPT coupling, the maximum pressure rating is 150 psi (10.5 Kgs/cm²)

FIGURE 1 (BOTH ENDS)




FIGURE 2

REVISIONS	DATE	CK'D	APP'D
A	11/10/89		

REVISIONS
 1. REVISIONS
 2. REVISIONS
 3. REVISIONS




FIGURE 3 (BOTH ENDS)





FIGURE 4 (BOTH ENDS)



INSTRUCTIONS

- 1) CUT CABLE (ITEM #1 OR #6) TO LENGTH SPEC. ON ORDER.
- 2) STRIP BOTH ENDS OF CABLE AS SHOWN IN FIGURE 1.
- 3) INSERT FERRULE (ITEM #2) ON THE CABLE AS SHOWN IN FIGURE 2, TYP. BOTH ENDS. INSERT SHIELD WIRE ASSY (ITEM #3) ON ONE END OF CABLE. CUT SHIELD WIRE COMING OUT OF PROBE TO 3 1/2" LONG & STRIP END. INSERT THIS WIRE ON OPPOSITE END OF CABLE. CRIMP BOTH ENDS USING AMP TOOL 59500 WITH INSERT 45066-3.
- 4) INSERT TERMINALS (ITEM #4) ON CENTER CONDUCTOR OF CABLE. (BOTH ENDS). CRIMP USING HAND CRIMP OR RATCHET TOOL. SEE FIG. 3.
- 5) PLACE SHRINK TUBE (ITEM #5) OVER CABLE ENDS AS SHOWN IN FIGURE 4. HEAT SHRINK AT LESS THAN 250°F FOR AT LEAST 30 SECONDS.

ASSY N°	DETAILS	DESCRIPTION
LRF11002.5	1 THRU 5	CABLE TERMINATION ASSY
LRF11002.6	2 THRU 6	HIT-TEMP CBL. TERM. ASSY.

CERTIFIED CORRECT FOR
 BY: _____ BINDICATOR CO.
 DATE: _____
 CUST. ORDER NO. _____
 OUR ORDER NO. _____
 REMARKS: _____

6	AR	CABLE HI STABILITY COAXIAL	LXC055209
5	1/46	SHRINK TUBING 20"	LXC035210
4	2	TERMINAL STA-KON	LXC050340
3	1	ASSY-SHIELD WIRE	LBI022140
2	2	FERRULE	LXU052120
1	A.R.	CABLE COAXIAL	LX0055208

DET.	RECD. SHY	DESCRIPTION	MAT. OR PART
UNSPECIFIED TOR.			
DECIMALS: 24			
ANGLES: 177			
DEBURR & BREAK EDGES: 208			

DRAWN	MEAL	APPROVED	PROOF
DATE	8 MAR 89	DATE	DATE
DEBURR & BREAK EDGES: 208		DATE	DATE
SCALE	NONE	DATE	DATE
TITLE	PROBE CABLE TERMINATION	DATE	DATE
EXT.	LAG: ASSYS	DATE	DATE

DO NOT SCALE DIMENSIONS ARE IN INCHES MATERIAL

BINDICATOR®
 PORT HURON, MICHIGAN 48060

REF

REVISIONS		DATE	APP'D
-	REDRAWN PER ECO#94-105	-	-
A	INSTR. 1 MODIFIED PER ECO 95-065	6/9 95 AC	<i>[Signature]</i>




FIGURE 1 (TYP BOTH ENDS)




FIGURE 2A (TYP BOTH ENDS)




FIGURE 2B (TYP BOTH ENDS)



FIGURE 3 (TYP BOTH ENDS)




FIGURE 4 (TYP BOTH ENDS)




FIGURE 5




FIGURE 6 (TYP BOTH ENDS)

ASS'Y NO.	DETAILS	DESCRIPTION
LRF110028	1 THRU 5 & 8	CABLE TERM. ASS'Y
LRF110029	2 THRU 7	HI TEMP. CABLE TERM. ASS'Y

8	AR.	WIRE # 20 AVG GREEN	LUCD35661
7	AR.	WIRE TEF GREEN	LUCD35351
6	AR.	CABLE HI STABILITY COAXIAL	LUCD35209
5	AR.	SHRINK TUBE	LUCD35210
4	AR.	TERMINAL STAKON	LUCD30340
3	2	ASS'Y SHIELD WIRE	LB0022140
2	2	FERRULE	LB0032120
1	AR.	FM- 62 COAXIAL CABLE	LUCD35208

DET. REQ'D	DESCRIPTION	MATERIAL PART
UNSPECIFIED TOL.		
DECIMALS MAX. ++		
ANGLES: + 1/2°		
DEBURR & BREAK EDGES .005		
DRAWN	APPROVED	PRD'D
ARIC C.	WJR	RB
DATE	DATE	DATE
8/1/94	8/3/94	8/4/94
SCALE	SIZE	PART OR DRAWING
FULL	B	LRF110028

- INSTRUCTIONS
- CUT CABLE (ITEM 1 OR 6) TO LENGTH SPECIFIED ON ORDER. (TO BE ONLY 12' LONGER THAN CONDUIT) (A)
 - STRIP BOTH ENDS OF CABLE AS SHOWN IN FIGURE 1.
 - INSERT THE FERRULE (ITEM 2) ON THE CABLE AS SHOWN IN FIGURE 2A & INSERT SHIELD WIRE (ITEM 3) AS SHOWN IN FIGURE 2B AND CRIMP AMP. TOOL 59500 WITH INSERT 45066-3.
 - INSERT TERMINALS (ITEM 4) ON CENTER CONDUCTOR OF CABLE & CRIMP USING HAND CRIMP OR RACHET (SEE FIGURE 3).
 - PLACE SHRINK TUBE (ITEM 5) OVER CABLE END AS SHOWN IN FIGURE 4 & HEAT SHRINK UNTIL SECURE FIGURE 5.
 - CUT GROUND WIRE ITEM 7 OR 8 4' LONGER THAN YOU CUT CABLE & STRIP BOTH ENDS AS SHOWN IN FIGURE 6.
 - INSERT TERMINALS (ITEM 4) & CRIMP USING HANDCRIMP OR RACHET (SEE FIGURE 6).


DO NOT SCALE DIMS. ARE IN INCHES

MATERIAL	FINISH

BINDICATOR®
PORT HURON, MICHIGAN 48060

TITLE REMOTE CABLE TERMINATION ASS'Y


REVISIONS	DATE	CK'D	APP'D
-----------	------	------	-------



OUTLINE DIMENSIONS


OPERATING INSTRUCTIONS:

To calibrate press and release the pushbutton on the module. The integral light will come on indicating that the calibration sequence has been initiated. When the light goes out, calibration is complete.



HOOKUP DIAGRAM

DO NOT SCALE DIMENSIONS ARE IN INCHES		FINISH		MATERIAL		DET.		REQ'D. SHT.		DESCRIPTION		MATERIAL OR PART			
						UNSPECIFIED TOL DECIMALS .XXX + ANGLES 1/2° DEBURR & BREAK EDGES .015		DRAWN BRUNTON		CHECKED BAR		APPROVED KAMP		PROD.	
				NEXT ASSY.		DATE 8 DEC 69		DATE 12 DEC 69		DATE 12 DEC 69		DATE 12 DEC 69		DATE 12 DEC 69	
										SCALE 12		PART OR DRAWING LKT 130107		PREVIOUS	
BINDERATOR® PORT HURON, MICHIGAN 48060		TITLE MANUAL DRAWING		REF. PART OR DRAWING											



HOOKUP DIAGRAM

OPERATING INSTRUCTIONS:


To calibrate, turn switch to "Calibrate" position and release. Red indicator light should come on indicating start of calibration. Light will go out when calibration is complete.

To test, turn switch to "Test" position and hold. If the RF-9000/10000 is in high level fail-safe mode, the RF-9000/10000 will "alarm" (1 to 6 seconds) assuming the unit was initially unalarmed (material not at probe).

If the RF-9000/10000 is in low level fail-safe mode, the unit will "unalarm" assuming the unit was alarmed initially (material not at the probe).

After testing, release the switch.

Note that the RF-9000/10000 electronics must be specially configured for testing.






OUTLINE DIMENSIONS

DO NOT SCALE
DIMENSIONS ARE IN INCHES

DET. REQ'D. SHT.		DESCRIPTION		MAT. OR PART	
UNSPECIFIED TOL. DECIMALS: XX.X	DRAWN: BRENTON	CHECKED: BOB	APPROVED: KANSY	PROD. DATE: 12-12-88	REF. LRF180108
ANGLES: 1/20	DATE: 8 DEC 88	DATE: 12-12-88	DATE: 12-12-88	DATE: 12-12-88	DATE: 12-12-88
DEBURR & BREAK EDGES 008	SCALE: NONE	SIZE: B	PART OR DRAWING: B	PREVIOUS: B	REF. LRF180108
NEXT ASS'Y.	TITLE: MANUAL DRAWING R.F. KEY SWITCH MODULE		REF. LRF180108		

BINDICATOR®
PORT HURON, MICHIGAN 48060

REVISIONS		DATE	CHK'D	APP'D
A	SPELLING ERROR RIGID WAS RIGID. RECOMMENDED WAS RECOMMENDED.	1/7/93	JN	RB
B	NOTE 5 ADDED PER ECD 95-065 AC	6/5/95	AS	AS
C	HARD AND SOFT WIRE NUTS ADDED PER ECD 95-111 AC	9/11/95	AS	AS



- NOTE: 1) FIELD WIRING SHALL BE ACCORDING TO LOCAL STD.
 2) POWER TO UNITS (TB2) 18 AVG MINIMUM RECOMMENDED.
 3) REFER TO DWG. # B-LRF110028-C FOR REMOTE CABLE TERMINATION.
 4) ON X/P UNITS, EXPLOSION PROOF SEAL FITTING MUST BE INSTALLED WITHIN 18" OF CONDUIT OPENING.
 5) COAX LENGTH TO BE ONLY 12" LONGER THAN CONDUIT





FIGURE 1




DET.	REQD.	SHT.	DESCRIPTION	MATERIAL	PART
UNSPECIFIED TOL.	DRAWN	CHECKED	APPROVED	PROD.	
DECIMAL XXX.XX	NEAL	SMH	RE	RB	
ANGLES + 1/2°	DATE	DATE	DATE	DATE	
DEDUR & BREAK	2/26/93	5/21/93	5/21/93	5/24/93	
LEDS .005	SCALE	SIZE	PART OR DRAWING		
	NONE	B	LRF180127		

DO NOT SCALE DIMS. ARE IN INCHES
 MATERIAL FINISH
 AC UNITS ARE MARKED NCU
 DC UNITS ARE MARKED GND
 AC UNITS ARE MARKED HOT
 DC UNITS ARE MARKED +VDC

TITLE
 RF10000 GP REMOTE PROBE CUSTOMER
 INSTALLATION/HOOKUP DWG. DL2 E/U



REVISIONS		DATE	BY	APPROVED
A	SPELLING ERROR, VESSEL WALL WAS VESEL WALL.	11/18/93	TB	[Signature]



13M-HM CAST CLAMP SIZE 1-1/2 CHERRY BURRELL 'S' OR LADISH TRI-CLAMP. (CUSTOMER SUPPLIED)

1.990 O.D. (50.55)

S.S. BIN CONNECTOR

40 MP-G TEFLON GASKET SIZE 1 X .875 I.D. CHERRY BURRELL 'S' OR LADISH TRI-CLAMP. (CUSTOMER SUPPLIED)

L14AM7 BUTT WELDING FERRULE SIZE 1 X .870 I.D. CHERRY BURRELL 'S' OR LADISH TRI CLAMP. (CUSTOMER SUPPLIED)

DO NOT SCALE DIM'S. ARE IN INCHES
BRACKETED. DIM'S ARE IN MM.



APPROX DIM'S	FLOODGRADE	STUB
E	14.25 (362)	14.25 (362)
D	6.00 (152.4)	2.75 (69.9)
C	3.62 (91.95)	2.00 (50.8)
B	2.38 (61.5)	1.50 (38)
A	.31 DIA. (8)	.31 DIA. (8)

DET. REQUISIT	DESCRIPTION	MAT. DR PART
UNDESIGNED TEL. DESIGNATION #	DRAWN	APPROVED
ANGLES & BREAK EDGES ARE	NEAL	RTR
	DATE	DATE
	8/17/93	8/18/93
	SCALE	SCALE
	NONE	NONE
	SIZE	SIZE
	B	B
	PART OR DRAWING	PART OR DRAWING
	LRF180130	LRF180130



TITLE	MANUAL DRAWING REMOTE PROBE W/TYPE 'S' MOUNTING
MATERIAL	FINISH
 BINDERATOR® PORT HURON MICHIGAN 48060	

REVISIONS

DATE	BY	APP'D



TYPE 'C' MOUNTING



TYPE 'B' MOUNTING

E	16.50 (419)	20.50 (521)	16.88 (428.75)	20.88 (530.35)	16.50 (419)
D	8.50 (216)	13.25 (336.5)	8.50 (216)	13.25 (336.5)	5.13 (130.3)
C	5.88 (149)	11.50 (292)	5.88 (149)	11.50 (292)	4.63 (117.6)
B	4.75 (121)	10.70 (271.8)	4.75 (121)	10.70 (271.8)	4.05 (103)
A	.31 DIA. (8)	.38 DIA. (9.5)	.31 DIA. (8)	.38 DIA. (9.5)	.31 DIA. (8)
APPROX DIM'S	STD. & FOODGRADE	H.D.	STD. KYNAR COATED	H.D. KYNAR COATED	STUB



DO NOT SCALE DIM'S. ARE IN INCHES
BRAK'ED, DIM'S ARE IN MM.

DET. REQ'D SHIT	DESCRIPTION	MATERIAL	SCALE	SIZE	TITLE
UNSPECIFIED FOR: DECIMALS: XX ANGLES: 1/2° EDGES: R0.5	CHECKED: [Signature] DATE: 10/27/93	DRAWN: NEAL DATE: 10/27/93	NONE	B	MANUAL DRAWING EXTENDED, REMOTE PROBE G/P & X/P
APPROVED: [Signature]	DATE: 11-5-93	PROB: [Signature]			
					PART OR DRAWING: LRF180137

BINDICATOR®
PORT HURON, MICHIGAN 48060

REVISIONS		DATE	CHK'D	APP'D

1-1/4" N.P.T. MOUNTING
 3/4" NPT CONDUIT OPENING
 EXT. GROUND SCREW



APPROX DIM'S	STD. & FOODGRADE	H.D.	STD. KYNAR COATED	H.D. KYNAR COATED
I	15.25 (387.5)	19.25 (489)	15.62 (396.7)	19.62 (498.35)
H	7.00 (178)	11.75 (298.5)	7.00 (178)	11.75 (298.5)
G	4.5 (114.3)	10.00 (254)	4.5 (114.3)	10.00 (254)
F	3.38 (86)	8.50 (216)	3.38 (86)	8.50 (216)
E	14.25 (362)	18.25 (463.5)	14.25 (362)	18.25 (463.5)
D	6.00 (152.5)	10.75 (273)	6.00 (152.5)	10.75 (273)
C	3.50 (89)	9.00 (228.5)	3.50 (89)	9.00 (228.5)
B	2.38 (60.5)	7.50 (190.5)	2.38 (60.5)	7.50 (190.5)
A	.31 DIA. (8)	.38 DIA. (9.5)	.31 DIA. (8)	.38 DIA. (9.5)

DO NOT SCALE DIM'S. ARE IN INCHES
 BRACKET, DIM'S ARE IN MM.



DET. REQ'D SHIT	DESCRIPTION	MATERIAL PART
UNAPPROVED FOR REVISIONS DATE DRAWN NEAL	CHECKED DATE APPROVED DATE	PROB DATE
AWLERS + J/P EDELBERG	DATE 11-3-93	DATE 11-5-93
SCALE NONE	SCALE NONE	SCALE NONE
TITLE MANUAL DRAWING REMOTE PROBE G/P W/TYPE 'A' MOUNTING	SIZE B	PART OR DRAWING LRF180138

BINDICATOR®
 PORT HURON, MICHIGAN 48060

REVISIONS

DATE/CD APPR

3/4" NPT CONDUIT OPENING
EXT. GROUND SCREW



CAUTION

WHEN MOUNTING EXPLOSION PROOF UNITS, NEVER ADJUST THE ORIENTATION OF THE PROBE OR PROBE HOUSING BY TURNING THE HOUSING SECTION. THIS WILL BREAK INTERNAL WIRES AND PERMANENTLY DAMAGE THE PROBE.
FOR TIGHTENING UNITS WITH THREADED BIN CONNECTIONS, THE UNIT MUST BE POSITIONED BY USING A WRENCH ON THE BIN CONNECTOR. WRENCH SIZE REQUIRED IS 1-1/16 INCH OPEN END.

APPROX DIM'S	STD. & FOODGRADE	H.D.	STD. KYNAR COATED	H.D. KYNAR COATED	STUB
E	14.25 (362)	18.25 (463.5)	14.62 (371.4)	18.62 (472.95)	14.25 (362)
D	6.00 (152.5)	10.75 (273)	6.00 (152.5)	10.75 (273)	2.63 (66.8)
C	3.50 (89)	9.00 (228.5)	3.50 (89)	9.00 (228.5)	2.25 (57.2)
B	2.38 (60.5)	7.50 (190.5)	2.38 (60.5)	7.50 (190.5)	1.75 (44.5)
A	.31 DIA. (8)	.38 DIA. (9.5)	.31 DIA. (8)	.38 DIA. (9.5)	.31 DIA. (8)

DO NOT SCALE DIM'S. ARE IN INCHES
BRACKETED DIM'S ARE IN MM.


DET. REQDSHT	DESCRIPTION	MAT. OR PART
UNSPECIFIED TOL. DECIMALS TO #	DRAWN	PROD.
ANGLES TO #	NEAL	DATE
EDGES .005	10/28/93	11-5-93
	CHECKED	DATE
	APPROVED	DATE
	SCALE	PART OR DRAWING
	NONE	B
		LRF180139

BINDICATOR®
PURT HURON, MICHIGAN 48060

TITLE MANUAL DRAWING
REMOTE PROBE UL X/P

DATE	CHK'D	APP'D

REVISIONS



'CAUTION'
 WHEN MOUNTING EXPLOSION PROOF UNITS, NEVER ADJUST THE ORIENTATION OF THE PROBE OR PROBE HOUSING BY TURNING THE HOUSING SECTION. THIS WILL BREAK INTERNAL WIRES AND PERMANENTLY DAMAGE THE PROBE.
 THE POSITION MUST BE ADJUSTED BY REMOVING THE MOUNTING BOLTS AND MOVING THE ENTIRE PROBE AND HOUSING.


- MOUNTING SURFACE PREPARATIONS**
1. LAY OUT TWO CONCENTRIC CIRCLES ON BIN WALL AT POINT WHERE THE RF LEVEL CONTROL IS TO BE MOUNTED. ONE CIRCLE TO BE 6-7/8" DIAMETER, THE OTHER 7-7/16" DIAMETER.
 2. CUT OUT 6-7/8" DIAMETER CIRCLE.
 3. LAY OUT SIX EQUALLY SPACED HOLES ON 7-7/16" DIAMETER CIRCLE. DRILL OR TAP FOR 1/4" BOLTS OR CAP SCREWS.

DO NOT SCALE DIM'S. ARE IN INCHES
 BRACKETED DIM'S ARE IN MM.

MATERIAL		FINISH		DESCRIPTION		MATERIAL PART	
UNSPECIFIED TOL.		DRAWN		CHECKED		APPROVED	
DECIMALS		NEAL		RIZ		BL	
ANGLES		DATE		DATE		DATE	
DEBURR & BREAK		10/28/93		11-5-93		11-5-93	
EDGES .005		SCALE		SIZE		PART OR DRAWING	
		NONE		B		LRF180141	
TITLE				MANUAL DRAWING			
REMOTE FLUSH PROBE				GP / XP			
BINDERATOR®				PORT HURON, MICHIGAN 48060			

REVISIONS

DATE	CHK'D	APP'D



9/32" DIA (7.14) HOLE ON A 7.44 (189) BOLT DIA. 6-PLC'S

3/4" NPT CONDUIT OPENING EXT. GROUND SCREW

4 OPTIONS CUSTOMER SPECIFIED
 CAUTION

WHEN MOUNTING EXPLOSION PROOF UNITS, NEVER ADJUST THE ORIENTATION OF THE PROBE OR PROBE HOUSING BY TURNING THE HOUSING SECTION. THIS WILL BREAK INTERNAL WIRES AND PERMANENTLY DAMAGE THE PROBE.
 THE POSITION MUST BE ADJUSTED BY REMOVING THE MOUNTING BOLTS AND MOVING THE ENTIRE PROBE AND HOUSING.



DO NOT SCALE DIM'S. ARE IN INCHES
 BRACKETED DIM'S ARE IN MM.

MOUNTING SURFACE PREPARATIONS

1. LAY OUT TWO CONCENTRIC CIRCLES ON BIN WALL AT POINT WHERE THE RF LEVEL CONTROL IS TO BE MOUNTED, ONE CIRCLE TO BE 6-1/8" DIAMETER, THE OTHER 7-7/16" DIAMETER.
2. CUT OUT 6-1/8" DIAMETER CIRCLE.
3. LAY OUT SIX EQUALLY SPACED HOLES ON 7-7/16" DIAMETER CIRCLE, DRILL OR TAP FOR 1/4" BOLTS OR CAP SCREWS.

MATERIAL		FINISH		DET. REQ. SHIT		DESCRIPTION		MAT. OR PART	
UNSPECIFIED TOL. DECIMALS XXX .XX .X		NEAL		CHECKER		APPROVED		PROB.	
ANGLES DEBURR & BREAK EDGES .005		DATE		DATE		DATE		DATE	
TITLE		SCALE		PART OR DRAWING		PART OR DRAWING		PART OR DRAWING	
BINDERATOR® PORT HURON, MICHIGAN 48060		NONE		B		LRF180143		LRF180143	

REVISIONS		DATE	CHK'D	APP'D



APPROX DIM'S	STD. & FOODGRADE	H.D.	STD. KYNAR COATED	H.D. KYNAR COATED	STUB
E	14.25 (362)	18.25 (463.5)	14.63 (371.6)	19.63 (498.3)	14.25 (362)
D	6.00 (152.5)	10.75 (273)	6.00 (152.5)	10.75 (273)	2.63 (66.8)
C	3.5 (89)	9.00 (228.6)	3.50 (89)	9.00 (228.6)	2.25 (57.2)
B	2.38 (60.5)	7.50 (190.5)	2.38 (60.5)	7.50 (190.5)	1.75 (44.5)
A	.31 DIA. (8)	.38 DIA. (9.5)	.31 DIA. (8)	.38 DIA. (9.5)	.31 DIA. (8)

DO NOT SCALE DIM'S. ARE IN INCHES
 BRAK'TED. DIM'S ARE IN MM.


MATERIAL FINISH

BINDICATOR®
 PORT HURON MICHIGAN 48060

TITLE MANUAL DRAWING
 LAGGED, REMOTE PROBE G/P & X/P

DET. REQD SHIT	DESCRIPTION	MATER PART
UNSPECIFIED TOL. ANGLES & L/W HATCH & BREAK DIMES ARE	CHECKED DATE 11-5-93	PKB
DRAWN NEAL	APPROVED DATE 11-5-93	PKB
SCALE NONE	SIZE B	PART OR DRAWING LRF180144

REVISIONS		DATE	BY	APP'D
A	6.50 DIMENSION ADDED PER ECO 94-134	10/7/94	V.R. AC	R.B.
B	METRIC DIM. TO GUARD WAS INCORRECT. IT WAS (2215.9), PER ECO#95-113	9/13/95		




DO NOT SCALE DIM'S. ARE IN INCHES
BRACKETED DIM'S ARE IN MM.

MATERIAL		FINISH		DET. REQ'D		DESCRIPTION		MATERIAL PART	
BINDICATOR® PORT HURON, MICHIGAN 48060				DESIGNED TO:	CHECKED:	APPROVED:	PROD:		
				USUAL PRACTICES:	RR	BL	R.B.		
				ANGLES & T/P:	DATE	DATE	DATE		
				EXERCISES:	10/28/93	11/5/93	11/5/93		
					SCALE	SIZE	PART OR DRAWING		
					NINE	B	LRF180146		
					TITLE		MANUAL DRAWING REMOTE CERAMIC PROBE		

REVISIONS

DATE	K/D	APP'D



DO NOT SCALE DIM'S. ARE IN INCHES
 BRACKETED DIM'S ARE IN MM.

DET. REQ'D SHIT		DESCRIPTION		MATER. PART	
UNDESIGNED TOL.	DRAWN	CHECKED	APPROVED	FINISH	
DESIGN	NEAL	FOR			
DATE	DATE	DATE	DATE		
12/10/93	12-13-93	12-13-93	12-13-93		
ANGLE'S & 1/2"	SCALE	SIZE	PART OR DRAWING		
EDGES AND	NDONE	B			
TITLE				MATER. PART	
RF10000 MANUAL DRAWING				LRF180147	
ELECTRONIC ENCLOSURE					

BINDICATOR®
 PORT HURON, MICHIGAN 48060

GENERAL TERMS AND CONDITIONS OF SALE

1. PAYMENT Terms of payment are Net 30 days and are effective from the actual date of invoice. If, in the Seller's opinion, the financial condition of the Buyer at any time-or any other circumstances do not justify the incurrence of production costs or shipment on the terms of payment specified, the Seller may require partial or full payment in advance.

2. F.O.B. All shipments are F.O.B. Seller's factory in Port Huron, Michigan, unless otherwise stated in the quotation.

3. QUOTATION AND PRICES Quoted prices are firm for thirty days and are subject to change without notice after expiration of this period. Orders calling for future deliveries will be invoiced according to prices in effect at the time of shipment.

4. TAXES Any applicable sales, use, revenue, excise or other taxes not specifically stated in the quotation are to be remitted by the Buyer directly to the appropriate regulatory agency.

5. EQUIPMENT WARRANTY/LIMITATION The following BINDICATOR products are warranted for a period of two years from date of shipment against defective materials and workmanship: RF Series, Mark III Yo-Yo, General Purpose Yo-Yo, Micro-Sonic Series, Eagle, Mach One, Leveldata, Tracker, and Levelite Series. All CELTEK and other Bindicator products are warranted for a period of one year from date of shipment against defective materials and workmanship. WE MAKE NO OTHER WARRANTY, EXPRESS OR IMPLIED, AND ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WHICH EXCEEDS THE FOREGOING IS HEREBY DISCLAIMED AND EXCLUDED FROM THIS CONTRACT. If the products are being acquired for resale, Buyer will make, in connection with any such resale, only those warranties contained herein and will indemnify us against any claims, causes of actions and judgements which arise from any representations, warranties or agreements made by or entered into by Buyer, other than those contained herein.

6. BUYER'S EXCLUSIVE REMEDY In the event of any breach of warranty, the sole and exclusive remedy of Buyer (or any person claiming through Buyer) shall be limited to the repair or replacement of defective products or parts, at our plant or at Seller's option, to the refund of the purchase price, provided that notice of such defects is given within six months after shipment. In no event will our liability include any incidental or consequential damages.

7. DELIVERY The Seller shall not be liable for loss or damage of any kind resulting from delay or inability to deliver or account of flood, fire, strike, labor troubles, riot, civil disturbances, accidents, acts or orders or regulations of civil or military authorities, shortages of materials, or any other cause or causes (whether or not similar in nature to any of these enumerated) beyond Seller's control.

8. PRODUCT CHANGES In keeping with our continuing policy of product improvement, we reserve the right to make changes in our products at any time, without incurring an obligation to change equipment previously shipped.

9. RETURN OF GOODS In no case may products or parts be returned without Seller's prior written permission. Products or parts returned under the aforementioned Equipment Guarantee must be shipped with transportation charges prepaid. All other returns must be shipped with transportation charges prepaid and will be subject to a restocking charge. Only products of standard Bindicator manufacture will be accepted for return. Products which are specially modified or produced to the Buyer's specifications will not be accepted for return.

10. CONTRACT FORMATION A binding contract shall not be effective until a written purchase order is received at Seller's office in Port Huron, Michigan and accepted in writing by an authorized employee of the Seller at its Port Huron office. The terms and conditions in our quotation or acknowledgment shall govern the contract and any different or additional terms in Buyer's purchase order, unless approved by Seller in writing, are hereby objected to.

11. CONSTRUCTION Any agreement arrived at shall be considered to be a Michigan contract and shall be construed under the laws of the State of Michigan.

12. CANCELLATION Request for cancellation must be in writing and referred to Bindicator. No orders will be accepted with the understanding that they may later be cancelled. If and when cancellation is approved by Bindicator, it is with the understanding that Bindicator will be fully reimbursed by payment of cancellation charge: which are to be determined by Bindicator.

13. CERTIFICATION OF NONSEGREGATED FACILITIES Our firm does not maintain facilities of a segregated nature contrary to the provision of 41 CFR 60-1.8, and further that if we have 50 or more employees and our contractual arrangements of \$50,000 or more we have complied with 41 CFR 60-1.7 concerning the annual filing of a report on Standard Form 100 (EEO-1) and with 41 CFR 60-1.40 by developing a written Affirmative Action Compliance Program.



150 Venture Boulevard
Spartanburg, SC 29306
Phone: (864) 574-8060, Fax: (864) 574-8063
Customer Service: (800) 778-9242
Internet: www.bindicator.com
Email: sales@bindicator.com