

TM - NEMA CONTROL

AC Reversing Contactors



B

AC Reversing Contactors - Bulletin 6031 TM

NEMA Size	Maximum Motor ² Horsepower Rating			Open Type	Catalog No. ¹
	200V	230V	460-575V		
00	1½	1½	2	See Vacuum Contactors in Section A	T31U03A -*
0	3	3	5		T31U030 -*
1	7½	7½	10		T31U031 -*
2	10	15	25		T31U032 -*
4	40	50	100		T31U034 -*
5 ²	75	100	200		
6	150	200	400		

Plug-Stop or Jogging Duty NEMA ICS 2-321-3

NEMA Size	Horsepower Ratings - Three Phase, 60Hz			
	200V	230V	380V	460/575V
0	1½	1½	1½	2
1	3	3	5	5
2	7½	7½	15	15
3	15	15	30	30
4	25	30	50	60
5	60	75	125	150
6	125	10/50	250	300

Ordering Information

- Use complete catalog number when ordering. Replace the (*) with the suffix from the coil table.
- Modifications page B36
- Engineering Data page B50.
- Renewal Parts page B42.
- Dimensions page B43.

Coil Volt/Hertz	Suffix
24/60 or 24/50	-96
110-120/60 or 110/50	-76
220-240/60 or 220/50	-26
440-480/60 or 440/50	-46
550-600/60 or 550/50	-56
200-208/60	-86

Notes:

1. Price includes contactor complete with one N.O. contact on each contactor. All contactors are mechanically and electrically interlocked.
2. For plug-stop or jogging duty, where operations exceed 5 times a minute, contactor size should be chosen in accordance with NEMA Standard ICS 2-321-3, as listed in table.